



TIPPERS AND DROPSIDES

ALUMINIUM REMOVABLE TIPPER



Industrial bodybuilder for Commercial Vehicles



ROBUSTNESS
& *Elegance*



www.bennes-jpm.com

ALUMINIUM REMOVABLE TIPPER

BODY

- Aluminium floor, 5083 H111 quality, 4 mm thick
- Reinforcing U-crossmembers, dim. 80x40, 350 mm pitch
- Aluminium tubular sideboards, 2.8 mm thick, 400 mm high, foldable and removable
- Locking-grips integrated in sideboards (3)
- Border fitting to band clamp
- Removable, steel, cone-shaped rear pillars, with 12 mm fixing bolts, cathaphoresis treated, 3 mm thick (4)
- Bulkhead 450 mm high
- Sideboard extension gussets, 100mm high, for 30mm thick sheets
- Aluminium double wing rear door, 2.8 mm thick, 450 mm high
- Wire mesh cab protection, removable, 4 mm diameter, galvanised steel
- Rear rolls, galvanised steel (2)

CRADLE

- Z-shaped frame rails, 158 mm high, 8 mm thick
- Centre distance 850 or 1060
- Hook height: 920 mm
- Steel gripper axis, diameter 30, welded to a steel pressed frame bolted to the structure (1)

FINISHING

- Shot-blasting
- Top coat: epoxy powder applied separately on each component
- Total coat thickness of 120 µm

OPTIONS

(non-exhaustive list)

- Removable and partly foldable sideboard extensions in steel or aluminium perforated sheet or in alu sheet metal
- Double wing or hinged rear door extensions
- Gantry
- Tool holder
- Rear door, gantry and sideboards protection
- Tarpauline
- Net
- Lashing points

the INTELLIGENT DESIGN

ROBUSTNESS

- ✓ All parts are powder-painted separately, 120 µm coat thickness
- ✓ Steel galvanised rear rolls (2)
- ✓ Steel cone-shaped pillars with fixing bolts (4)
- ✓ Aluminium sideboards (tipper sideboards version)

PRACTICAL

- ✓ More payload
- ✓ Interchangeability left/right sideboards
- ✓ Border fitting to band clamp
- ✓ Sealing guaranteed by a lip on sideboards
- ✓ Many options with bolt system

SERVICE

- ✓ Two-year warranty
- ✓ Solid customer service
- ✓ A JPM technical interlocutor is at your disposal



Versions

Painted kit
Painted and assembled

Weight *

3200 mm : 360 kg
3500 mm : 380 kg
* approx. indication

BENNES JPM

PRODUCTION AND HEAD OFFICE
RN 88 - 12800 Naucelle - France
Tel: (33) 0565692470
Fax: (33) 0565692377
contact@bennes-jpm.com

Distributor's stamp

www.bennes-jpm.com