

# TIPPERS AND DROPSIDES

# STEEL REMOVABLE TIPPER



**Industrial bodybuilder for Commercial Vehicles** 





# STEEL REMOVABLE TIPPER

#### **BODY**

- S355 steel floor, 30/10 mm thick side-members, with reinforcing U-crossmembers, dim. 50x40x3 mm, 350 mm pitch
- S355 steel tubular sideboards, 2 mm thick, laser seam-welded, 400 mm high, foldable, removable and interchangeable (3)
- Locking-grips integrated in sideboards
- Border fitting to band clamp
- Removable, steel, cone-shaped rear pillars, with 12 mm fixing bolts, cataphoresis treated, 3 mm thick (2)
- Bulkhead 450 mm high
- Sideboard extension gussets, 100mm high, for 30mm thick sheets
- E36 steel double wing rear door, 20/10 mm thick, 450 mm high
- Wire mesh cab protection, removable, 4 mm diameter, galvanised
- Rear rolls, galvanised steel (1)

#### CRADLE

- PIPE 140 frame rails
- Centre distance 850 or 1060
- Hook height: 920 mm
- Gripper axis, diam. 30, welded on tubular structure of 120x60 (4)

#### **FINISHING**

- Shot-blasting
- Powder-painting applied separately on each component
- Top coat: epoxy powder applied separately on each component
- Total coat thickness of 120 µm and protection from salt spray from up to 1.000 hours

#### **OPTIONS**

(non-exhaustive list)

- Removable and partly foldable sideboard extensions in steel or aluminium perforated sheet or in alu sheet metal
- Double wing or hinged rear door extensions
- Gantry
- Tool holder
- Rear door, gantry and sideboards protection
- **Tarpauline**
- Net
- Lashing points

#### the INTELLIGENT DESIGN

# ROBUSTNESS

- ✓ All parts are powder-painted separately, 120 µm coat thickness (priming + top coat)
- ✓ Protection from salt spray from up to 1.000 hours
- ✓ Steel galvanised rear rolls (1)
- ✓ Cone-shaped pillars with fixing bolts (2)
- ✓ High shock resistance due to doublewalled sideboards

# A PRACTICAL

- ✓ Interchangeability left/right sideboards
- ✓ Interchangeability steel/alu sideboards
- boards
- Border fitting to band clamp
- Sealing guaranteed by a lip on sideboards

## SERVICE

- ✓ Two-year warranty
- Solid customer service
- disposal









#### Versions

Pre-treated kit Painted kit Painted and assembled

## Weight \*

3200 mm: 530 kg 3500 mm: 560 kg approx. indication



PRODUCTION AND HEAD OFFICE RN 88 - 12800 Naucelle - France Tel: (33) 0565692470

Fax: (33) 0565692377 contact@bennes-jpm.com Distributor's stamp

